IDP-17, 17" INDUSTRIAL FLOOR MODEL DRILL PRESS

354300

Accuracy, stability and versatility are the benchmark features of the JET 17" and 22" Industrial Drill Presses. This heavy-duty industrial line of JET Drill Presses come standard with oversize tables and are CSA/CUS Certified. JET backs their machines with the industry-leading Two Year Warranty.



FEATURES

- For added Safety, the IDP-17, 17" Industrial Floor Model Drill Press follows strict guidelines and electrical requirements to be certified by the CSA Group.
- Spindle is supported by high quality ball bearings
- Hinged metal belt and pulley cover coupled with quick adjustment motor mount allow rapid changing of spindle speeds
- Large Hand Grips designed with the users comfort in mind
- Rotating, 45° tilting, crank-operated worktable with quick release clamp
- A 1/2" diameter external positive depth stop with three nut locking feature for quick adjustment
- Adjustable tension spindle return spring
- Drill chuck and key attach to the side of the drill press always within reach of the operator
- On/off switch located on front of the drill press head
- Heavy Duty construction
- Cast Iron table and base
- Table ground for accuracy
- STANDARD EQUIPMENT
- LED Machine Lamp
- Ground Table
- · Spindle Safety Guard

· Drill Chuck and Key





JET RED ASSURANCE 2-YEAR WARRANTY

JET warrants every product it sells. If one of our tools needs service or repair, one of our Authorized Service Centers located throughout the United States can give you quick service. In most cases, any of these JPW Industries Authorized Service Centers can authorize warranty repair, assist you in obtaining parts, or perform routine maintenance and major repair on your JET tools. For the name of an Authorized Service Center in your area call 1-800-274-6848.

STAND BEHIND YOUR WORK JET



IDP-17, 17" INDUSTRIAL FLOOR MODEL DRILL PRESS

354300

SPECIFICATIONS

Style (Type)	Belt Drive
Drills to Center of Circle (in)	17
Drilling Capacity Cast Iron (In.)	3/4
Drilling Capacity Mild Steel (In.)	5/8
Distance Column to Spindle (In.)	8-3/8
Number of Spindle Speeds	12
Range of Spindle Speeds (RPM)	350 - 2,800
Column Diameter (In.)	3-1/8
Spindle Taper (In. x TPI)	MT-2
Spindle Travel (In.)	3-5/16
Spindle Distance to Base (In.)	50
Spindle Distance to Table (Max.) (In.)	30-1/2
Table Size (L x W) (In.)	14 x 14
T-Slots Number and Size (In.)	2 and 1/2
T-Slot Centers (In.)	9/16
Base Dimensions (In.)	21-3/4 x 13-3/4 x 2-3/16
Base Work Table (In.)	16-15/16 x 10-13/16







